



Beschreibung

Die Feuermeldezentrale Syncro ASM ist eine adressierbare Alarmzentrale für maximal 2 Schleifen mit jeweils bis zu 126 Feuermeldern und Alarmgebern. Mehrere Einheiten können über den RS485- Bus zu einem größeren System zusammengeschlossen werden. Standardmäßig beinhaltet die Feuermeldezentrale 8 konfigurierbare potentialfreie Ein- und Ausgänge, welche durch Zusatzkarten erweitert werden können (Zulassungen in Vorbereitung).

Die Feuermeldezentrale Syncro ASM erfüllt die Anforderungen von EN54-2 und EN 54-4 und ist für den Einsatz auf Seeschiffen geeignet.

- Zulassungen: LR, GL, DNV, KR, CCS, ABS, MED

Description

The Syncro ASM is an analogue addressable Alarm Panel for maximal 2 loops, each supporting up to 126 detectors and alarm devices. Several units can be interconnected to a more complex system via the RS485- bus. By default the Alarm Panel includes 8 configurable voltage free in- and outputs that can be augmented with supplemental cards (approvals pending).

The Fire Alarm Panel Syncro ASM is in compliance with EN54-2 and EN54-4 and is suited for service in seagoing vessels.

- Approvals: LR, GL, DNV, KR, CCS, ABS, MED